

Superior startability, gradeability and low-speed manoeuvrability.

Proven reliability and durability of Eaton Fuller® 13- and 18-speed transmissions.

Platforms:

- Multipurpose High Performance (MHP)
- Multipurpose Extreme Performance (MXP)

Built upon the robust Fuller 13- and 18-speed manual transmissions, the UltraShift *PLUS* Performance Series uses an electronic clutch actuator to provide faster shifting and smoother engagement. Intelligent shift selection software uses changes in grade, weight and throttle to calculate the most efficient and effective shift points. The UltraShift *PLUS* fully engages the clutch at idle, giving the driver ultimate control in challenging situations.

Technical Features

- Fully automated two-pedal design (no clutch pedal)
- Electronic Clutch Actuator (ECA) provides smooth engagement
- On/Off-highway performance design
- Safety features include auto neutral and Intelligent Hill Start Aid, which prevents roll-back and roll-forward while launching on grades using foundation wheel brakes
- Automatic, Manual and Low modes offer driver full control
- Creep Mode
- Paired to the highest torque engines available today with torque capacities ranging from 1450 lb-ft (1966 Nm) through 2250 lb-ft (3050 Nm)
- World class startability and ratio coverage



Powering Business Worldwide

BACKED BY

Roadranger

SUPPORT

UltraShift® PLUS Performance Automated Transmissions

Total System Installed Specifications (Dry)

SPECIFICATIONS	CAPACITY	WEIGHT*	LENGTH**	SPEEDS
FO-14E313A-MHP	1450 lbs. ft. [1966 Nm]	978 lbs. [444 kg]	40.61 in. [1031.49 mm]	13 forward, 3 reverse
FO-16E313A-MHP	1650 lbs. ft. [2237 Nm]	978 lbs. [444 kg]	40.61 in. [1031.49 mm]	13 forward, 3 reverse
FO-18E313A-MHP	1850 lbs. ft. [2508 Nm]	978 lbs. [444 kg]	40.61 in. [1031.49 mm]	13 forward, 3 reverse
FO-20E313A-MHP	2050 lbs. ft. [2779 Nm]	978 lbs. [444 kg]	40.61 in. [1031.49 mm]	13 forward, 3 reverse
FO-14E318B-MXP	1450 lbs. ft. [1966 Nm]	978 lbs. [444 kg]	40.61 in. [1031.49 mm]	18 forward, 4 reverse
FO-16E318B-MXP	1650 lbs. ft. [2237 Nm]	978 lbs. [444 kg]	40.61 in. [1031.49 mm]	18 forward, 4 reverse
FO-18E318B-MXP	1850 lbs. ft. [2508 Nm]	978 lbs. [444 kg]	40.61 in. [1031.49 mm]	18 forward, 4 reverse
FO-20E318B-MXP	2050 lbs. ft. [2779 Nm]	978 lbs. [444 kg]	40.61 in. [1031.49 mm]	18 forward, 4 reverse
FO-22E318B-MXP	2250 lbs. ft. [3051 Nm]	978 lbs. [444 kg]	40.61 in. [1031.49 mm]	18 forward, 4 reverse

* Dry weight, including clutch ** Standard install length

Ratios and Steps

Model	Reverse				Overall Ratio	Forward Gears																		
	R4	R3	R2	R1		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	
MHP		4.03	12.85	15.06	16.84	12.29	8.51	6.05	4.38	3.20	2.29	1.95	1.62	1.38	1.17	1.00	0.86	0.73						
					% Step	44	41	38	37	40	17	20	17	18	17	16	17							
MXP	3.43	4.03	12.85	15.06	19.73	14.40	12.29	8.51	7.26	6.05	5.16	4.38	3.74	3.20	2.73	2.28	1.95	1.62	1.38	1.17	1.00	0.86	0.73	
					% Step	17	44	17	20	17	18	17	17	17	17	20	18	20	17	18	17	16	17	

Driver Interface Simple and Intuitive

- Manual override available
- Low mode
- Button shifting in drive, reverse, manual and low modes

Driveline Protection Features

- Stall prevention
- Engine Overspeed Protection
- Clutch Abuse Protection
- Auto gear select
- Hill Start Aid

Supported by the Roadranger Network

- OEM dealer, fleet familiarity
- Parts and service widely available
- Does not require service by a dedicated service network
- Modular design minimizes cost and time of service
- Roadranger field service force provides training and support at dealership and fleet level
- Advanced electronics facilitate comprehensive diagnostic capabilities

BACKED BY

Roadranger

SUPPORT

For sales, service or technical assistance, call **1300 432 866**, for more time on the road. Or visit our web site at www.roadranger.com.

Roadranger: Eaton and other trusted partners providing the best products and services in the industry, ensuring more time on the road.

Eaton Vehicle Group
Rowville, Victoria, 3178
Australia.(03) 9751 8800
Roadranger.com

© 2012 Eaton Corporation
All rights reserved.
Printed in Australia. 12/12

Note: Features and specifications listed in this document are subject to change without notice and represent the maximum capabilities of the software and products with all options installed. Although every attempt has been made to ensure the accuracy of information contained within, Eaton makes no representation about the completeness, correctness or accuracy and assumes no responsibility for any errors or omissions. Features and functionality may vary depending on selected options.



Powering Business Worldwide